

# P3ESR XD2



# Harbeth®

**P3ESR XD2**

Technical Information



HANDMADE IN ENGLAND  
[www.harbeth.co.uk](http://www.harbeth.co.uk)

Harbeth Audio Ltd., 3-4 Enterprise Park, Lindfield, West Sussex, RH16 2LH, UK



## Technical Specifications

**Description:** P3ESR XD2 loudspeaker

### Technical features

**Drive unit** 1 x 110mm Harbeth-made RADIAL4 mid/bass unit  
1 x 19mm ferrofluid-cooled tweeter

**Frequency range** 75Hz - 20kHz,  $\pm 3$ dB free-space, grille on, smooth off-axis response

**Impedance** 6 ohms, easy to drive

**Sensitivity** 83dB/2.83V/1m axial

**Amplifier suggestion** Works with a wide range of amplifiers - suggested from 15W/channel

**Power Handling** 50W programme

**Connectors** Two 4mm Harbeth-branded binding posts

**Space needs** Ideally > 0.30m from the rear wall

**Stands** Optimally to bring ears level with tweeters (tweeter: 230mm up from cabinet base)

### Dimensions

**Height** 306mm

**Width** 190mm

**Depth** 184mm (+12mm for grille and binding posts)

**Weight** 6.1kg each (without packing)

**Finish** Black Ash  
Cherry  
Oak  
Walnut  
Rosewood



This information is intended as a guide only and reflects the current specification at the time of print.  
We reserve the right to make changes to the specification.