



T-Series

Home Theater System

www.polkaudio.com



T-Series

product information sheet

Polk Audio T-Series

Introduce Yourself To Polk Audio Performance and Value

T-Series speakers are perfect for building your first home theater or stereo listening system, whether you have a small room, or just want a great value priced speaker for multi-room applications. T-Series speakers reproduce sound accurately with impressive volume. They're solidly built and come in a black wood grain finish. Best of all, simply add a PSW Series powered subwoofer yourself with real home theater performance.

Polk speakers are designed and engineered by Polk Audio, Inc. at our research and development facilities in Maryland and California.

Specifications, dimensions and features subject to change without notice. For more information call us at 1-800-377-7655 (USA and Canada). Outside of North America call +1 (410) 358-3600.

All T-Series speakers feature:

- Premium home theater and music performance.
- Polk Audio's exclusive Dynamic Balance drivers and tweeters for wide response and low distortion.
- Wide dispersion drivers and tweeters project sound over a wide area so every listener in a room hears open, "box-less," three dimensional sound.
- Front mounted bass port for deep, punchy bass.
- High efficiency design allows them to be driven by unpretentious amplifiers and receivers, revealing that classic Polk sound—open, spacious and clear.
- 5-way binding posts provide a wide array of secure wire-hookup options.
- Easy Setup - Tower speakers feature integrated stand (no setup required) and the bookshelf speakers include keyhole slot for quick and easy wall mounting.

Specifications	T15	T30	T50
Speaker Use	Bookshelf	Center	Floor standing
Driver Complement			
Mid/Woofer	1 - 5 1/4" Diameter	2 - 5 1/4" Diameter	1 - 6 1/2" Diameter; 2 - 6 1/2" Bass Radiator
Tweeter	1 - 3/4" Diameter	1 - 1" Diameter Wave Guide Tweeter	1 - 1" Diameter Wave Guide Tweeter
Electrical			
Overall Frequency	60Hz – 24kHz	38Hz – 24kHz	38Hz – 24kHz
Crossover	2-way	2-way	2-way
Response			
Lower	-3dB Limit 65Hz	-3dB Limit 40Hz	-3dB Limit 40Hz
Upper	-3dB Limit 20kHz	-3dB Limit 20kHz	-3dB Limit 20kHz
Nominal Impedance	8 ohms	6 ohms	6 ohms
Recommended Watts/Channel	20 – 100 Watts/channel	20 – 100 Watts/channel	20 – 100 Watts/channel
Amplifier Power			
Efficiency	89 dB	90 dB	90 dB
Inputs	5-way binding posts	5-way binding posts	5-way binding posts
Maximum Power Handling	150W	100W	150W
Dimensions			
Cabinet Size	10 5/8" H x 6 1/2" W x 7 1/4" D	6.5" H x 19" W x 7.5" D	36.25" H x 7.75" W x 8.75" D
Mounting Options	Wall mount with integrated key-hole slot	NA	NA
Enclosure Type	Vented	Vented	Bass Reflex
Shipping unit	Pair	Single	Single
Speaker Warranty	5 years parts and labor (original purchaser)	5 years parts and labor (original purchaser)	5 years parts and labor (original purchaser)
Recommended Optional Accessories	30 – 36" speaker stands	NA	NA