



RB-1590
Stereo Power Amplifier
PRELIMINARY



RB-1590

Stereo Power Amplifier

Power - refined, detailed, and plenty of it. Rotel's new Class AB stereo power amplifier is rated at 350 watts per channel into 8 ohms both channels driven. That is a lot of power, but larger listening rooms or less sensitive loudspeaker designs require it to bring out the best possible performance and attain realistic audio dynamics.

The impressive capabilities of this amplifier begin with a solid foundation consisting of twin, massive toroidal transformers custom made by Rotel. These transformers are just part of a rock-solid power supply that includes eight special British made BHC capacitors, known for their low loss and quick response times. These components will continue to supply all of the voltage and current requirements needed, even under the most difficult load conditions.

But power unrefined has never been a Rotel design goal. Every aspect of circuit design has been carefully considered and each component has been rigorously selected after extensive listening sessions. The circuit topography has been laid out in a true monoblock design ensuring maximum signal separation and improved stereo imaging.

Features include: XLR Balanced and RCA input connections, two pair of 5-way speaker binding posts, 12-volt trigger control, thermal protection circuitry, over-current, over-voltage protection circuitry, dual staged power on relay to reduce surge current and extend longevity, and a detachable IEC power cord all in a 5 U chassis with included rack ears.

The RB-1590 has been designed for the most discerning audio enthusiast and will provide the highest levels of audio performance.



SPECIFICATIONS

Continuous Power Output (20 - 20kHz, <0.03%, 8 ohms)	350 watts/channel	Signal to Noise Ratio (A weighting)	120 dB
Total Harmonic Distortion (20Hz - 20kHz, 8 ohms)	<0.03%	Channel Separation	>64 dB
Intermodulation Distortion (60Hz : 7kHz, 4 : 1)	<0.03%	Input Impedance/Sensitivity	
Frequency Response (±0.5 dB)	10Hz - 100kHz	Unbalance	12k ohms / 2.2 V
Damping Factor (1kHz, 8 ohms)	300	Balance	100k ohms / 3.5 V
Speaker Impedance	4 ohms minimum	Gain	
		Unbalance	27.5 dB (±0.5 dB)
		Balance	23.5 dB (±0.5 dB)
		Power Requirements	
		USA	120 volts, 60 Hz
		EC	230 volts, 50 Hz
		Power Consumption	
		Standby	< 0.5 watts
		BTU (4 ohms, 1/8th power)	2100 BTU/h
		Dimensions (W x H x D)	431 x 237 x 454mm
			17 x 9 3/8 x 17 7/8 in
			5U / 221mm / 8 3/4 in
		Front Panel Height	
		Weight (net)	38.1kg, 84 lb

Rotel of America
54 Concord St.
N. Reading, MA 01864 USA
T +1 978 664 3820
F +1 978 664 4109

www.rotel.com